



EDGE 0W-40 A3/B4

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Castrol EDGE, boosted with **TITANIUM FST™**, provides outstanding oil strength, giving you the confidence to demand maximum engine performance from today's modern, higher revving sports, performance and luxury vehicles requiring lower viscosity higher performance oils.

Castrol EDGE is our strongest and most advanced range of engine oils. Its **TITANIUM FST™** gives up to double the strength against oil film breakdown while reducing friction between metal surfaces.

Castrol EDGE with **TITANIUM FST™**: helping your engine perform at its best.

Application

Castrol EDGE 0W-40 A3/B4 is suitable for use in automobile, gasoline and diesel engines where the manufacturer recommends an ACEA A3/B3, A3/B4, API SN/CF or earlier specification 0W-40 lubricant.

Castrol EDGE 0W-40 A3/B4 is approved for use in vehicles from leading manufacturers please refer to the specifications section and your owners handbook.

Conditions of Use

Castrol EDGE 0W-40 A3/B4 gives you the confidence to demand maximum engine performance from today's modern, higher revving sports, performance and luxury vehicles requiring a high level of protection and higher performance low viscosity oils.

Castrol EDGE 0W-40 A3/B4

- Maximises short and long term engine performance
- Improves engine efficiency, independently qualified
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Reduces engine deposits to help maximise engine response
- Exceed high performance standards set by premium car manufacturers including all FPV models, modern European and Japanese prestige vehicles

Typical Characteristics

Name	Method	Units	Castrol EDGE 0W-40 A3/B4
Density @ 15C, Relative	ASTM D4052	g/ml	0.844
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.2
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5600
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	74
Viscosity Index	ASTM D2270	None	181
Pour Point	ASTM D97	°C	-57
Flash Point, PMCC	ASTM D93	°C	209
Ash, Sulphated	ASTM D874	% wt	1.13

Product Performance Claims

ACEA A3/B3, A3/B4
API CF/SN
Meets Ford WSS-M2C937-A
MB-Approval 229.3/ 229.5
Porsche A40
VW 502 00 / 505 00

EDGE 0W-40 A3/B4

21 Dec 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk