

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name:MOGUL DIESEL L-SAPS 5W-30Date of issue:03. 10. 2012Revision date:24. 4. 2019 (Version 1.2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDER-TAKING

1.1 Product Identifier

MOGUL DIESEL L-SAPS 5W-30

Chemical name: Mixtures

Registration No.: None Index No.: None

1.2 Relevant identified uses of the substance/mixture and uses advised against

Designated uses: Motor oil Uses of the mixture not recommended: The product may not be used in any way other than those specified in sections 1 and 7.

1.3 Details of the supplier of the safety data sheet

Name:	PARAMO, a.s.	
Place of business:	Přerovská 560, 530 06 Pardubice, Czech Republic	
Phone:	+420 466 810 111	
Fax:	+420 466 335 019	
E-mail:	paramo@paramo.cz	
Website:	www.paramo.cz	
Person(s) responsible for this Safety Data Sheet: <u>bl@paramo.cz</u>		

1.4 Emergency telephone number

Control Room of PARAMO, a. s.: +420 466 303 175 Toxicological Information Centre at Na Bojišti 1, 128 08 Prague 2, phone (Czech Republic only) (24 hours, 7 days a week): +420 224 919 293, 224 915 402, 224 914 575 Transport Information & Accident System (**TRINS**), phone: +420 476 709 826

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008 (CLP) the product is not classified as hazardous.

2.2 Label elements

Pictogram: None

Warning description: None

Dangerous substances: None

Standard phrases of hazard: None

Safe handling instructions: None

Other requirements: None

2.3 Other hazards

The product is not persistent, bioaccumulative and toxic chemical substance or very persistent and very bioaccumulative chemical substance according to the criteria set out in Annex *XIII* to the EC (PBT, vPvB). Prolonged or frequently repeated exposure to this product may cause eye and skin irritation. The inhalation of oil mist may irritate the breathing passages.

Flammable liquid. The risk of combustion arises when heated above flash point.

The product is not expected to cause long-term adverse effects in the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

It is not a substance.



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

 Date of issue:
 03. 10. 2012

 Revision date:
 24. 4. 2019 (Version 1.2)

3.2 Mixtures

Chemical characteristics

The mixture of the following substances and admixtures:

The mixture contains these hazardous substances and substances with the highest admissible concentrations in the working atmosphere.

Identification numbers	Substance name	Content in % weigh	Classification according to (ES) č. 1272/2008	Note.
EC: 265-157-1 CAS: 64742-54-7 Registration number: 01-2119484627-25	Distillates (petroleum), hydrotreat- ed heavy paraffinic	50 - 80	Asp. Tox. 1, H304	L
EC: 253-249-4 CAS: 36878-20-3 Registration number: 01-2119488911-28	Bis(nonylphenyl)amine	0.1 - 2.5	Aquatic Chronic 4, H413	
EC: - CAS: - Registration number: polymer	Branched calcium alkylphenate sulphide, alcalic	0.1 - 2.5	Aquatic Chronic 4, H413	

Note. L: The mineral oil has DMSO value <3% - it is not classified as carcinogenic.

Full texts of H-phrases are quoted in Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

If the first aid treatment is to be administered, release tight clothing and keep the exposed person warm and at rest. If conscious, place the exposed person to the stabilised position and get prompt medical attention. In case of cardiac arrest, apply cardiac massage and call medical assistance immediately. If unconscious but breathing, place the exposed person to the stabilised position and call medical assistance immediately.

The first aid instructions are structured according to separate exposure ways:

Inhalation: In case of inhalation of the aerosol, dispose of the affected person to fresh air.

Skin contact: In case of contact with the skin, wash the affected area thoroughly with water and soap and treat with a suitable cream.

Contact with eyes: Check for contact lenses and remove them, if present. Rinse the eyes thoroughly with ample quantity of clean (lukewarm, if possible) water for at least 15 minutes. If eye irritation persists, seek medical assistance.

Ingestion: Rinse mouth with water, never induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None

4.3 Indication of any immediate medical attention and special treatment needed

Inhalation: Check for breathing and pulse rate of the affected person. Do not induce vomitting.

Ingestion and inhalation: Contraindications: induced vomiting and gastric irrigation. Administration of medicinal charcoal has no effect. The affected person must be monitored at least for the period of 48 to 72 hours. Monitoring for pulmonary oedema symptoms starts six hours after the ingestion/inhalation and it continues at least for the period of 48 to 72 hours.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing means: Heavy, medium and light air-mechanical foam, type B or C fire-extinguishing powders.

Unsuitable extinguishing means: Water jet (for cooling only).

5.2 Special hazards arising from substance or mixture

Combustion products and hazardous gases: smoke, carbon monoxide, carbon dioxide.



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

 Date of issue:
 03. 10. 2012

 Revision date:
 24. 4. 2019 (Version 1.2)

5.3 Advice for firefighters

Fire-fighting teams exposed to smoke or vapours must wear respiratory and eye protection. In confined spaces, the teams must use a self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Prevent any contamination of clothing/footwear with the product; prevent any contact with skin and eyes. Use suitable protective clothing; if contaminated, change the clothing immediately. Remove any potential source of ignition. Strictly no smoking or naked flames. If possible, larger spills may be covered with foam in order to control the creation of vapours and aerosols. Provide for good ventilation of the affected areas. All persons not taking part in rescue operations must be kept away to a sufficient distance.

6.2 Environmental precautions

Act as quick as possible, do not allow to enter drains, underground water or watercourses and soil by enclosing the affected area (damming, closing of gulleys). Notify the relevant authorities.

6.3 Methods and material for containment and cleaning up

If possible, contain the spillage and pump off or remove the product mechanically or draw it off the water surface. Let absorb any residua or smaller quantities to a suitable sorbent (Vapex, Chezacarb, saw dust, sand) and place it into labelled containers for further disposal in accordance with the relevant waste disposal legislation.

6.4 Reference to other sections

Apart from the instruction set out in this Section, other important information is shown in section 8 - EX-POSURE CONTROLS AND SECTION 13 – DISPOSAL CONSIDERATIONS.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

All fire-safety measures must be followed while handling the product. Strictly *no smoking* or *naked* flames. In addition, it is necessary to avoid any inhalation of vapours or aerosol, contamination of skin and/or eyes. If handling of heavy containers is necessary, use suitable handling equipment and avoid of any possibility of slipping. Do not eat, drink and smoke at work. Store the product away from foodstuffs, drinks and fodder.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly closed containers or packing in places protected from rain, dust, heat and other weather. Protect against the ingress of water and mechanical impurities. The maximum storage temperature is 40 °C.

7.3 Specific end use(s)

Motor oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

The mixture contains substances for which exposure limits are set for the working environment.

<u>Mineral oil</u>

PEL (Czech Rep., Government Regulation No. 246/2018 Sb.)	mineral oil (aerosols): 5 mg/m ³	
NPK-P (Czech Rep., Government Regulation No. 246/2018 Sb.)	mineral oil (aerosols): 10 mg/m ³	
AGW (Germany, TRGS 900)	mineral oil (aerosols): 5 mg/m ³	
NDS (Poland , Dz.U. 2014 poz. 817)	mineral oil (aerosols): 5 mg/m ³	
NPEL - average (Slovakia, Government Regulation No. 355/2006 Coll.) mineral oil (aerosols): 1 mg/m ³		
NPEL - short-time (Slovakia, Government Regulation No. 355/2006	6 Coll.) mineral oil (aerosols): 3 mg/m ³	



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

Date of issue:	03. 10. 2012
Revision date:	24. 4. 2019 (Version 1.2)

DNEL inhalation/workers/long-term local influence: DNEL inhalation/workers/long-term systemic influence: DNEL dermal/workers/long-term systemic influence: DNEL oral/public/long-term systemic influence: PNEC (oral predators): 5.6 mg/m³ 2.7 mg/m³ 1 mg/kg body weigh/day 0.74 mg/kg body weigh/day 9.33 mg/kg food

8.2 Exposure controls

Observe general safety and hygienic measures; do not eat, drink and smoke at work. After washing the skin with warm water and soap, treat it preventively with a regeneration cream.

Eye/face protection: Use protective goggles or safety eyewear (face shield).

Skin protection: Use protective gloves resistant against oil products and tested according to EN 374; best of all made of nitrile or neoprene rubber.

Respiratory protection: Not necessary, if the vapour concentration in air is less than the concentration limits. If the opposite is the case or aerosols are created, use emergency escape mask with A, AX (brown) filters or any other mask types suitable of protecting against organic gases and vapours.

Thermal hazard: None

Environmental exposure controls: It is necessary to prevent leakage into the environment by all available means.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Appeulatioe			
State (20 °C):	liquid		
Colour:	brown		
Odour:	typical		
Odour threshold value:	not determined		
pH:	no determination necessary		
Pour point:	< -36 °C		
Initial boiling point and boiling range: not determined			
Flash point OK:	> 210 °C		
Vaporisation rate:	not determined		
Flammability(solids, gases): IV. Class			
Upper/lower explosion or flammability limits: not determined			
Vapour pressure:	< 10 Pa at 20 °C		
Vapour density:	not determined		
Relative density:	855 kg/m³ at 15 °C		
Solubility:	insoluble in water		
Separation factor:	n-octanol/water: not determined		
Self-ignition temperature:	350 °C		
Decomposition temperature: not determined			
Viscosity:	9.3 to 12.5 mm ² /s/100 °C		
Explosive properties:	not explosive		
Oxidation properties:	not oxidising		
Other information			

9.2 Other information

Combustion point: 230°C

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No reactivity danger exists.

PARAMO

SAFETY DATA SHEET

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name:MOGUL DIESEL L-SAPS 5W-30Date of issue:03. 10. 2012Revision date:24. 4. 2019 (Version 1.2)

10.2 Chemical stability: Stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions: No dangerous reactions are possible.

- **10.4 Conditions to avoid:** Creation of concentrations within the explosion limits, presence of ignition sources and contact with a naked flame.
- **10.5** Incompatible materials: Strong oxidisers.
- **10.6 Hazardous decomposition products:** Under normal conditions: none; if burning under deficiency of air, carbon monoxide may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

<u>Mineral oil</u>

Acute toxicity: oral toxicity (rat) $LD_{50} > 5\ 000\ mg/kg\ (OECD\ 401)$

dermal toxicity (rabbit) LD₅₀ > 2 000 mg/kg (OECD 402)

inhalation toxicity (rabbit) $LC_{50} > 5000 \text{ mg/m}^3$ (OECD 403)

Chronic toxicity: chronic inhalation toxicity NOAEC > 220 mg/m³ (OECD 412)

Skin corrosion/irritation: OECD 404 test results proved no the skin irritation.

Serious eye damage/irritation: OECD 405 test results proved no eye irritation.

Respiratory or skin sensitization: the respiratory organ sensitisation data are missing, but no such sensitisation is expected. As regards the sensitisation by skin contact, OECD 406 tests were made and no sensitisation proved.

Germ cell mutagenicity: data is missing

Carcinogenicity: Carcinogenic activity induced by repeated dermal irritation can be avoided by minimizing contact with the skin.

Reproduction toxicity: data is missing.

STOT - single exposure: not determined

STOT – repeated exposure: not determined

Aspiration hazards: May be fatal if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION

Based on acute toxicity of invertebrates and algae, the product is classified as toxic to the environment, H412.

12.1 Toxicity

<u>Mineral oil</u>

Acute toxicity for aquatic environment: fish - LL_{50} (96 hrs) > 100 mg/l, NOEL ≥ 100 mg/l (OECD 203) algae EL_{50} (72 hrs) ≥ 100 mg/l (OECD 201)

invertebrates EL_{50} (48 hrs) > 10 000 mg/l, NOEL \geq 1000 mg/l (OECD 202)

Chronic toxicity for aquatic environment: invertebrates NOEL (21 days) 10 mg/l, fish NOEL (21 days) 10 mg/l Toxicity for soil microorganisms and for soil macroorganisms: none

12.2 Persistence and degradability: Not expected - the substance is not soluble in water.

12.3 Bioaccumulative potential: Not expected

- 12.4 Mobility in soil: Not expected
- **12.5 Results of PBT and vPvB assessment:** The product does not contain substances meeting the criteria for PBT or vPvB in accordance with Annex XIII, Regulation (EC) No 1907/2006 (REACH), as amended.
- 12.6 Other adverse effects: Not expected



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

 Date of issue:
 03. 10. 2012

 Revision date:
 24. 4. 2019 (Version 1.2)

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Substance disposal procedures: Do not dispose of together with municipal waste. Do not dispose of waste through sewers. Waste, impaired product or unused/surplus product must be handed over to the person authorised for waste disposal according to the local law.

Waste Code: N 13 02 05, in sorbent: N 15 02 02

Contaminated packaging disposal procedures: The containers with product residua must be placed on the place specified by the municipal authorities or handed over to the person authorised for waste disposal.

Waste legislation: Directive 2008/98/EC

SECTION 14: TRANSPORT INFORMATION

Nomenclature and labelling according to the European Agreement concerning the International Carriage of Dangerous Goods, Road (ADR)/Rail (RID)

ADR: Not regulated as a dangerous good RID: Not regulated as a dangerous good ADN: Not regulated as a dangerous good IATA-DGR: Not regulated as a dangerous good IMDG-Code: Not regulated as a dangerous good

- 14.1 UN Number: none, not regulated as a dangerous good
- 14.2 UN proper shipping name: none, not regulated as a dangerous good
- 14.3 Transport hazard class(es): none, not regulated as a dangerous good
- 14.4 Packing group: none, not regulated as a dangerous good
- 14.5 Environmental hazard: none
- 14.6 Special precautions for user:

Petroleum liquids under the Act on the waters, as amended, considered dangerous because of the requirements of the quality of surface and groundwater when transporting large volumes necessary to follow the advice of Standard 75 3418.

14.7 Transport in bulk according to Annex II of MARPOL and IBC Code: not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- ✓ Act on Clean Air Protection, as amended later, incl. connected regulations and rules. The product does not represent a volatile organic substance pursuant to Act on Clean Air Protection, as amended and relevant regulations of the Ministry of Environment.
- ✓ ČSN 65 0201 Flammable Liquids manufacturing, storage and handling premises According to ČSN 65 0201, the product is classified in the IV Flammability Class.
- ✓ ČSN 33 0371 In explosive electrical installation Explosive mixtures Classification and methods of testing According to ČSN 33 077, the product is classified in the T3 Thermal Class and IIA Explosive Class.
- ✓ Government Regulation No. 361/2007 Coll., by which the conditions of occupational health and safety are stipulated, as amended later.
- ✓ ČSN 75 3415 Protection of water against oil products. Premises for oil product handling and storage.
- ✓ Act No. 350/2011 Coll., on chemical substances and chemical preparations, and on amendments of some acts.
- ✓ Regulation (EU) No. 2015/830 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- ✓ Regulation (EC) No. 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

The chemical safety assessment has been made for mineral oil



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

 Date of issue:
 03. 10. 2012

 Revision date:
 24. 4. 2019 (Version 1.2)

SECTION 16: OTHER INFORMATION

Standard safety phrases (H-phrases) used in the safety data sheet:

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Safe handling instructions (P-phrases) used in the safety data sheet: None

Abbreviations used in the safety data sheet ADR European Agreement concerning the International Carriage of Dangerous Goods by Road Aquatic Chronic Hazardous to the aquatic environment Asp. Haz./Tox. Aspiration hazard / toxicity Carc. Carcinogenicity CAS **Chemical Abstract Service** CLP Regulation of Classification, Labelling and Packaging Derived no-effect level DNEL Half maximal effective concentration EC_{50} EINECS European Inventory of Existing Commercial Chemical Substances EC European Community number Eve Dam./Irrit. Eye Damage / Irritation Flammable Liquid Flam. Liq International Air Transport Association IATA International regulation for Construction and Equipment of Ships carrying Dangerous IBC Chemicals in Bulk IC₅₀ half maximal inhibitory concentration International Civil Aviation Organization **ICAO** IMDG International Maritime Dangerous Goods Code ISO International Organization for Standardization LC₅₀ / LD₅₀ Median lethal dose Measures of pollutant concentration LOAEC Lowest-observed-adverse-effect level LOAEL Log Kow Octanol-water partition coefficient MARPOL International Convention for the Prevention of Pollution from Ships Mutagenicity Mutag. Measures of pollutant concentration NOAEC No-observed-adverse-effect level NOAEL No Observed Effect Concentration NOEC NPK Highest admissible concentration OECD TG **OECD** Guidelines for the Testing of Chemicals PBT Persistent, bioaccumulative and toxic PEL Acceptable Exposure Limit PNEC Predicted no-effect concentration parts per million ppm REACH Europion Union Regulation for Registration, Evaluation, Authorisation and Restriction of Chemicals Reproductive toxicity Repr. European treaty on the international transport of hazardous substances by rail RID Skin Corr./Irrit./Sens. Skin Corrosion/ Irritation/ Sensitisation STOT SE Specific target organ toxicity - single exposure STOT RE Specific target organ toxicity - repeated exposure UN The four-digit identification number of the substance or object taken from the UN Model Regulations UVCB Compounds of unknown or variable composition, complex reaction products or biological materials VOC Volatile organic compounds vPvB Highly persistent and highly bioaccumulative



According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 2015/830

Product name: MOGUL DIESEL L-SAPS 5W-30

 Date of issue:
 03. 10. 2012

 Revision date:
 24. 4. 2019 (Version 1.2)

Other information important for the safety and health of humans

The product must not be used for any purpose other than those specified in sections 1 and 7 without the manufacturer's / importer's specific consent. The user is responsible for compliance with all relevant health protection regulations.

Training

The user is obliged to get acquainted with the safety precautions relating to the product handling / treatment and complete applicable trainings at the workplace before he/she starts to work with the product.

Information on changes

- ✓ The change has been made on the basis of the Commission Regulation (EU) No. 453/2010 coming into effect.
- ✓ The change (Version 1.0) Classification CLP
- The change (Version 1.1) art. 1.2, 1.3, 2.1, 2.2, 3.2, 8.1, 9.1, 14, 15.1, 16.
- ✓ The change (version 1.2) art. 1, 2, 3, 4, 5.2, 7, 8.1, 9.1, 11, 12, 13, 16.

Statement: The Safety Data Sheet has been prepared in accordance with REACH Regulation (EC) No 1907/2006. It contains the data that are needed to ensure safety and health at work and environmental protection. These data do not replace the quality specification and cannot be considered as a guarantee of the suitability and usability of this product for a specific application. These data correspond to the current state of knowledge and experience and are in accordance with our valid legal regulations. The customer is responsible for compliance with the applicable regional legislation