

Eni i-Ride moto 20W-50



APPLICATIONS

Eni i-Ride moto 20W-50 is an innovative lubricant with top synthetic formula, designed and developed by Eni search to meet the lubrication requirements of 4-stroke motorcycle engines with high specific powers.

CUSTOMER ADVANTAGES

- The formulation of **Eni i-Ride moto 20W-50** stands out for its low volatility and high thermo-oxidative stability which ensure excellent engine performance and reduced oil consumption.
- The detergent and dispersing qualities of **Eni i-Ride moto 20W-50** are the result of a careful selection of the components included in the formulation, which results in effective control on the formation of deposits such as sludge, lacquers and of carbonaceous type.
- The viscosimetric properties associated with the chosen formulation technology give the product a high ability to effectively counteract wear phenomena resulting in the protection of the mechanical parts of the engine.
- **Eni i-Ride moto 20W-50** has an exceptional mechanical shear resistance, a prerequisite for all motorcycles with combined engine gearbox lubrication.

SPECIFICATIONS - APPROVALS

- API SL
- JASO MA, MA2



Eni i-Ride moto 20W-50



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	852
Viscosity at 100°C	ASTM D 445	mm ² /s	19.0
Viscosity at 40°C	ASTM D 445	mm ² /s	141
Viscosity Index	ASTM D 2270	-	153
Viscosity at -15°C	ASTM D 5293	mPa·s	9000
Flash point (COC)	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-48

