



SPRAY BODY CALIPER PAINT

Technical Data Sheet No 836

VOC compliant with the regulations

Silicone Aerosol Paint

Recommended for the painting of objects which are exposed to temperatures of up to 300°C (572°F)

Excellent results

General Technical Description

2-3 passes

Dust free 10 min at 23°C (73°F)

Surface

For the painting of metal objects which are exposed to temperatures of up to 300°C (572°F)

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL / BODY 771 ANTISIL FAST

Make sure the surface is first wiped dry and then air dried.



Make sure you always use appropriate face protection and good ventilation

Product Application: »» Apply on objects which are exposed to temperatures up to 300°C (572°F). Apply two to three medium coats necessary to cover the area waiting 5-10 min in between each coat. Each coat should appear uniform and dry before the next one is applied.



Shake well before using

Flash Point:
-97°C (-142.6°F)

Specific Gravity:
1,019 g/cm³



2-3 coats approximately 20-30 microns (0.78-1.2 mil)

Solid Content (No thinner):
35% Weight

VOC (2004/42/EC)
This product is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 770g/L. 2004/42/II(b)(840)770



Dust free 10 min at 23°C (73°F)



Heat for 30-60 min at 160-200°C (320-392 °F) to achieve hardening

Theoretical Coverage:
-

Cleaning of equipment:
-

Remarks:

- Always try to use the product in accordance with the specifications provided.
- It can be used by countries that do not adopt the VOC legislation as well.
- Shake thoroughly before use.
- Shake for 1-2 mins after agitator ball has started to rattle. After preparing the area to be painted ensure it to be free from dirt, wax, oil etc. Test on a similar surface using a back and forth action.
- Optimum operating temperature range 10-25°C (50-77°F).

Storage shelf life:

Store in a cool place and use within 36 months for best results.

+5 to +25°C (41-77°F).

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 4/2017, October 2017